

Indoor drop coaxial cable - 75 Ohm
Indoor installation cable (Screening Class B)



CAVEL Code:

KF114

Pag. 1/2

Constructive Data

Inner conductor of plain copper	(Cu)	Ø 1,13 mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 mm
Water repellent sealing (dielectric)	(Jelly1)	
Copper/Polyester tape longitudinally overlapped	(Cu/Pet)	
Braid of annealed copper wires	(Cu)	Ø
Braid optical coverage (IEC 96-1)		37 %
Outer sheath of Polyvinylchloride white lead-free (Q1B)	(PVC)	Ø 6,60 ± 0,10 mm
printed each meter by black ink-jet :	(ss=week, aa=year) (m=meter marking)	

CAVEL KF 114 MADE IN ITALY 75 Ohm EN50117-2-4 ss/aa m

Mechanical Parameters

Weight of copper conductors	17,20	kg/km
Total weight of cable	40,60	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Max. cable pulling strength	150	N

Electrical Parameters

Characteristic impedance (@ 200 MHz)	75,00 ± 3,00	Ohm
Capacitance (@1kHz)	52,00 ± 2,00	pF/m
Velocity factor	85 %	
Inner conductor resistance	18,0	Ohm/km
Outer conductor resistance	22,0	Ohm/km
loop Resistance	40,0	Ohm/km
Maximum current (Ieff)	8,0	A
Insulation voltage of the sheath (spark test)	3,0	kV
Comply to the Standard:	EN50117-2-4	

-Attenuation-

Frequency (MHz)	5	10	30	50	200	300	470	862	1000	1750	2150	2400	3000
dB/100m	1,40	2,00	3,00	3,70	7,80	9,60	12,20	16,90	18,40	25,00	28,00	29,60	33,50

Structural return loss (SRL)

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>26 dB
2000 - 3000 MHz	>22 dB

Transfer impedance

5 - 30 MHz 2 mOhm/m

Screening attenuation (SA)


30 - 1000 MHz	>75 dB
1000 - 2000 MHz	>85 dB
2000 - 3000 MHz	>75 dB



Attenuazione di schermatura / Screening Attenuation

Cavo classe B / B Class Cable

Cavo tipo / Cable type : **KF 114**



Standard Packaging

Mod 8A Shrink Pack	100 m in thermoretractable material	6 coils per package = 600 m
Mod 10 Shrink Pack	250 m in thermoretractable material	2 coils per package = 500 m

Connectors

BNCC703SL	BNC male compression connector for outdoor installation
F703	F male crimp connector for indoor installation
FA703	F male twist-on connector for indoor installation
FC703SL	F male compression connector for outdoor installation